



WARNING LIGHTING | DIRECTIONAL LIGHTING | LIGHTBARS | WHITE LIGHTING | REVERSING SAFETY



6500 SERIES SAE Class II Strobe

ECCO's 6500 Series strobe light offers outstanding value when a cost-effective SAE Class II light is required. Featuring a shock-resistant five-point power supply mounting and robust reinforced polypropylene base, this series of lights are suitable for both on- or off-highway applications. Thread-on polycarbonate lens and snap-fit flashtube allow easy field service without tools. Model-specific options include double or quad flash patterns.

Models

PART NO.	PROFILE	VOLTAGE	AMPS	FPM	MOUNT
6550A	Low	12-48	2.4	80 x2 or 65 x4	3 Bolt Flange / 1" Pipe
6570A	Medium	12-48	2.4	80 x2 or 65 x4	3 Bolt Flange / 1"Pipe
6550A-VM	Low	12-24	2.4	80 x2	Vacuum-Magnet
6570A-VM	Medium	12-24	2.4	80 x2	Vacuum-Magnet
6550A-HBT	Low	12-24	2.4	80 x2	Semi-Permanent HBT
6570A-HBT	Medium	12-24	2.4	80 x2	Semi-Permanent HBT

Features and Benefits

- Robust reinforced polypropylene base
- Thread-on polycarbonate lens and snap-fit flashtube allows easy field service
- Shock-resistant circuit board mounting incorporates 5 support points
- · Consistent operation during voltage and temperature changes
- Temperature Range: -22°F to +122°F (-30°C to +50°C)
- Warranty: Strobe = 2 years / Flashtube = 6 months

120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120° 120°

Parts & Accessories

- Flashtube: R6501FT
- Lenses Low/Medium Profile: Amber - R6050LA/R6070LA
- Blue R6050LB/R6070LB
- Clear R6050LC/R6070LC
- Green R6050LG/R6070LG
- Red R6050LR/R6070LR

T 800-635-5900 orders@eccogroup.com