

## WEATHER-TITE™ PERMAPLUG™

Blocks debris from entering the socket

**LECTRACOIL™ Jacketing\***  
Jacketing has excellent recoil memory, and is chemical and abrasion resistant

**Large Finger Grips**  
Large finger grips for easy coupling/uncoupling

**Unbreakable housing**  
Non-corrosive unbreakable housing for long life and durability

**Replaceable Seal**  
The WEATHER-TITE™ seal is field replaceable in under two minutes (P/N: 5-750)

**Floating Brass Pins**  
Floating brass pins for secure installation in mis-aligned sockets

**WEATHER-TITE™ Seal**  
Blue nitrile, three-ring seal stops magnesium chloride and other debris from entering the socket



\*Also available in straight ABS LECTRAFLEX™

### ABS LECTRACOIL™



1/8, 2/10 & 4/12 ga.

30-9120	10', with WEATHER-TITE™ PERMAPLUGS™
30-9320	12', with WEATHER-TITE™ PERMAPLUGS™
30-9620	15', with WEATHER-TITE™ PERMAPLUGS™
30-9920	15', 48" lead, with WEATHER-TITE™ PERMAPLUGS™
30-9820	20', 48" lead, with WEATHER-TITE™ PERMAPLUGS™

- Recommended for ABS applications and trailers with high voltage demands
- Flexible from -82°F to 195°F (-63°C to 91°C)
- Excellent recoil memory, chemical and abrasion resistance

### ABS PERMACOIL™



1/8, 2/10 & 4/12 ga.

30-4320	12', with WEATHER-TITE™ PERMAPLUGS™
30-4420	12', 48" lead, with WEATHER-TITE™ PERMAPLUGS™
30-4620	15', with WEATHER-TITE™ PERMAPLUGS™
30-4920	15', 48" lead, with WEATHER-TITE™ PERMAPLUGS™
30-4820	20', 48" lead, with WEATHER-TITE™ PERMAPLUGS™

- Recommended for ABS applications
- Flexible from -87°F to 150°F (-66°C to 66°C)
- Good recoil memory, chemical and abrasion resistance

For new and innovative products, visit [www.phillipsind.com](http://www.phillipsind.com)

## DURACOIL™



1/10 & 6/12 ga.

22-9320	12', with WEATHER-TITE™ PERMAPLUGS™
22-9620	15', with WEATHER-TITE™ PERMAPLUGS™
22-9720	15', 72" lead, with WEATHER-TITE™ PERMAPLUGS™

- For standard 7-way applications, NON-ABS equipped trailers
- Flexible from -82°F to 195°F (-63°C to 91°C)
- Excellent recoil memory, chemical and abrasion resistance

## NON-ABS PERMACOIL™



1/10 & 6/12 ga.

22-4320	12', with WEATHER-TITE™ PERMAPLUGS™
22-4620	15', with WEATHER-TITE™ PERMAPLUGS™

1/12 & 6/14 ga.

24-4320	12', with WEATHER-TITE™ PERMAPLUGS™
24-4620	15', with WEATHER-TITE™ PERMAPLUGS™

- For standard 7-way applications, NON-ABS equipped trailers with minimum voltage demands
- Flexible from -87°F to 150°F (-66°C to 66°C)
- Good recoil memory, chemical and abrasion resistance

## Straight ABS LECTRAFLEX™



1/8, 2/10 & 4/12 ga.

30-2010	8', with WEATHER-TITE™ PERMAPLUGS™
30-2030	10', with WEATHER-TITE™ PERMAPLUGS™
30-2050	12', with WEATHER-TITE™ PERMAPLUGS™
30-2070	15', with WEATHER-TITE™ PERMAPLUGS™

- Spring-wrapped compression contact pins
- Chemical and abrasion resistant
- Flexible from -40°F to 150°F (-40°C to 66°C)
- Available in 3-IN-1 and 4-IN-1 assemblies

## 3-IN-1 and 4-IN-1 Combo Assemblies



1/8, 2/10 & 4/12 ga.

### 3-IN-1 ELECTRICAL & AIR ASSEMBLIES

30-2150	12', with WEATHER-TITE™ PERMAPLUGS™, rubber air lines
30-2170	15', with WEATHER-TITE™ PERMAPLUGS™, rubber air lines
30-2190	20', with WEATHER-TITE™ PERMAPLUGS™, rubber air lines

1/8, 2/10 & 4/12 ga.

### 4-IN-1 ELECTRICAL & AIR ASSEMBLIES - Single Pole

30-2250	12', ABS with WEATHER-TITE™ PERMAPLUGS™, single pole, rubber air lines
30-2270	15', ABS with WEATHER-TITE™ PERMAPLUGS™, single pole, rubber air lines
30-2290	20', ABS with WEATHER-TITE™ PERMAPLUGS™, single pole, rubber air lines

### 4-IN-1 ELECTRICAL & AIR ASSEMBLIES - Dual Pole

30-2256	12', ABS with WEATHER-TITE™ PERMAPLUGS™, dual pole, rubber air lines
30-2276	15', ABS with WEATHER-TITE™ PERMAPLUGS™, dual pole, rubber air lines
30-2296	20', ABS with WEATHER-TITE™ PERMAPLUGS™, dual pole, rubber air lines

- Recommended for ABS applications
- Spiral wrapped for a clean organized look
- Outstanding kink and abrasion resistance
- Includes hanging clamp and clip for easy installation (P/N 5-5018)



For new and innovative products, visit [www.phillipsind.com](http://www.phillipsind.com)

12070 Burke Street, Santa Fe Springs, CA 90670  
800.423.4512 Fax 800.597.7757

# PHILLIPS